

nylosolv[®] A

Fast and efficient washout solvent for safe processing of photopolymer printing plates

Be
brilliant.

Product features

- + Ideal for high quality processing of conventional and digital photopolymer printing plates
- + High flashpoint allows washout at higher temperatures
 - + faster washout time
 - + less plate swelling
 - + less drying time
 - + improved safety in transit and in storage
- + Optimised formulation with a three component mixture of hydrocarbons and alcohol
- + Easy distillation under vacuum, with minimal loss of components and convenient component adjustment
- + Low odour for comfortable work
- + Gentle and environmentally friendly

Safety and technical information*

Optimal washout temperature	35 °C 95 °F
Flashpoint	> 63 °C > 145 °F
Transport and Storage	See material safety data sheet
Ignition temperature	200 °C 392 °F
Density	0.841 g/cm ³ (20 °C 68 °F)
Packing Unit	30 l/can 200 l/barrel 950 l/ibc container

*Please find further information in our nylosolv[®] User Guide.

Please contact us for additional information.

info@xsyglobal.com • www.xsyglobal.com

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of XSYS's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted. Product names followed by [®] are trademarks registered by XSYS Germany GmbH and/or its affiliates.



XSYS

Print solid. Stay flexible.